626 - Retaining Wall Systems

Effective Date: May 16, 2012 Revised: April 20, 2014

Contact: Sammy J. Searls (304) 558-9866

Email: <u>sammy.j.searls@wv.gov</u>

This is an approved list of vendors and does not remove the requirements for the designs and materials to be approved prior to use as per Section 626 of the Standard Specifications.

See the Bridge Design Manual, Table 3.10.1.4B for applications of these wall systems and limitations which include:

- 1. No utilities shall be permitted in the reinforced fill zone.
- 2. Reinforcement shall not be exposed to soils with low resistivity (< 3,000 ohm-cm), high sulfates (200 ppm), or high chloride (100 ppm) contents.
- 3. Not to be used in areas with unpredictable erosion or having uncontrolled scour below the reinforced fill zone.

Mechanically Stabilized Earth (MSE) Retaining Wall Systems

(Precast Concrete Panel Wall Systems)

			,
System	Manufacturer	Approval Number	Approved Fabricators
Heigh	t Limited to 60 Feet		
Retained Earth	Foster Geotechnical, Division of LB Foster Springfield, VA (F054J)	1349757A	Cherry Precast – Rural Hall, NC KJ Williams – Cumberland, MD
Reinforced Earth	The Reinforced Earth Company Vienna, VA (R170A)	1349758A	Cherry Precast – Rural Hall, NC KJ Williams – Cumberland, MD
ISOGRID	The Neel Company Springfield, VA (N123A)	1349759A	
MSE Plus	SSL Scotts Valley, CA (S423A)	1349760A	
Tricon	Tricon Precast, Ltd. Houston, TX (T183A)	1380649A	
Heigh	t Limited to 50 Feet	1	1
EarthTrac	EarthTec, Inc. Purcellville, VA (E136A)	1393169A	

Sine Wall	Sine Wall LLC West Chester, OH (S452A)	1399093A		
Heigh	Height Limited to 40 Feet			
Ares	Tensar Earth Technologies, Inc. Atlanta, GA (T173A)	1349761A		

MSE Wire-Faced Retaining Wall Systems

System	Manufacturer	Approval Number
Height	Limited to 60 Feet	
Retained Earth	Foster Geotechnical, Division of LB Foster Springfield, VA (F054J)	1349762A
Reinforced Earth	The Reinforced Earth Company Vienna, VA (R170A)	1349763A
MSE Plus	SSL Scotts Valley, CA (S423A)	1349764A
Height	Limited to 40 Feet	
Mesa ^{a b}	Tensar Earth Technologies, Inc. Atlanta, GA (T173A)	1349766A
Ares ^a	Tensar Earth Technologies, Inc. Atlanta, GA (T173A)	1349761A

^a Can only be used as a temporary system for a maximum of three (3) years

^b Must be constructed with the high performance connector

The Modular Block Wall Systems listed below are approved with the following limitations:

- No utilities shall be permitted in the reinforced fill zone.
 Not to be used in areas with erosion or scour below the reinforced fill zone.
- 3. Concrete must comply with requirements of Section 626.5.1.1.1.
- 4. Block size tolerances must comply with the requirements of Section 626.5.1.1.2

MSE Modular Block Wall Systems

System	Manufacturer	Approval Number	Licensed Producer
CLASS I - H	leight Limited to 40 Feet		
KeySystem 1	Keystone Retaining Wall Systems, Inc. Minneapolis, MN (K116A)	1349765A	
Mesa	Tensar Earth Technologies, Inc. Atlanta, GA (T173A)	1349766A	
Landmark	Anchor Wall Systems, Inc. Minnetonka, MN (A317A)	1349767A	Peerless Block & Brick Co. St. Albans, WV
Magnum Stone	SSL Scotts Valley, CA (S423A)	1422575A	Rhodes Brick & Block Co. St. Albans, WV
Redi-Rock Positive Connection System	Redi-Rock International Charlvoix, MI (R183A)	1425060A	Foster Supply, Inc. Scott Depot, WV Mount Clare, WV Harrodsburg, KY
CLASS II - H	leight Limited to 20 Feet (Note: Cla	ss I may be subst	ituted)
ReCon	ReCon Retaining Wall Systems, Inc. St. Louis Park, MN (R182A)	1424718A	Peerless Block & Brick Co. St. Albans, WV
CI ASS III - H	leight Limited to 10 Feet (Note: Cla	sses I or II may be	substituted)

Anchor	Anchor Wall Systems, Inc. Minnetonka, MN (A317A)	1349768A	
Genesis	Anchor Wall Systems, Inc. Minnetonka, MN (A317A)	1349769A	
Keystone	Anchor Wall Systems, Inc. Minnetonka, MN (A317A)	1349770A	
Redi-Rock °	Redi-Rock International Charlvoix, MI (R183A)	1386514A	Foster Supply, Inc. Scott Depot, WV Mount Clare, WV Harrodsburg, KY
Redi-Scapes	Redi-Rock International Charlvoix, MI (R183A)	1386514A	Foster Supply, Inc. Scott Depot, WV Mount Clare, WV Harrodsburg, KY
ReCon	ReCon Retaining Wall Systems, Inc. St. Louis Park, MN (R182A)	1424719A	Peerless Block & Brick Co. St. Albans, WV

CLASS IV - H	eight Limited to 5 Feet (Note: Cla	sses I, II, or III may be	substituted)
Anchor	Anchor Wall Systems, Inc. Minnetonka, MN (A317A)	1349771A	
Keystone	Anchor Wall Systems, Inc. Minnetonka, MN (A317A)	1349772A	
Redi-Rock ^d	Redi-Rock International Charlvoix, MI (R183A)	1386515A	Foster Supply, Inc. Scott Depot, WV Mount Clare, WV Harrodsburg, KY

 $^{\mbox{\scriptsize d}}$ Allowed up to 10 feet with 41" deep blocks. Limited to 5 feet with 28" deep blocks.